


25 XPL Easy Loader Series 25 Ton Tag with Lift Front Axle



Capacity: 50,000 lbs. Trailer Weight: 11,720 lbs.
Deck Width: 8 ft. 6 in. Length: 22 ft. Height: 34 in.
Hi Tensile V-50 Steel Mainframe
Pierced Crossmembers
Cold-Formed Drawbar & Nose Plate

Heavy Duty 2-Speed Jack
Drawbar Storage Area
8° Beaver Tail (Safe Low Loading Angle)
Patented "ROTO RINGS"® Swivel 360°
100% Sealed Modular Wiring Harness

SPECIFICATIONS

Frame	Mainrails: W14" x 26 lbs. wide flange I-Beam, one piece cold formed Hi-tensile 50,000 P.S.I. steel mainrails from front to drawbar to rear of trailer
Crossmembers	6" x 9 lbs. per ft. I-Beam pierced through mainbeam
Decking	Nominal 2" Hardwood
Headboard	8" high, full width of trailer Drawbar Storage Area
Lights	Sealed L.E.D., 12 volt, DOT approved
Wiring Harness	USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug
Hitch	One piece solid cast steel (adjustable) lunette eye & flange mount
Safety Chains	Two 1/2" Blue-Krome plated high test, safety hook w/ latch
Parking Jack	70,000 lbs. static / 40,000 lbs. lift, (Heavy Duty 2-Speed screw type)
Tie Down	Six per side - Patented "ROTO RINGS"® Swivel 360°
Colors	Yellow (Standard), Red, Black w/ RPC Undercoating

RUNNING GEAR

Tires	Twelve 215/75R17.5 (H) Michelin Steel Belted Radial
Hubs	Six Hub Piloted Disc Type Hubs with Outboard Brake Drums
Wheels	Twelve 6.75 x 17.5, 8-Bolt, Hub-Piloted Disc Wheels
Suspension <input type="checkbox"/> <input type="checkbox"/>	(1) Hutch H-9700, Three leaf, capacity 50,000 lbs. Tandem
<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	(1) Cush CLC-25-005 Air Ride with Lift, capacity 25,000 lbs.
Axles	Three 5" diameter 20,000 lbs. each, H.M. series bearings (maximum axle track width)
ALL WHEEL ABS	Anti-Lock Brake System 4S3M Sensors on (2) Axles Three Modulator Valves
Parking Brake	Spring Brakes on All Axles

OPTIONS

- Additional Deck Length & Width (23'-24'-25' Optional Lengths) (96" Optional Width)
- Additional "ROTO-RINGS"®
- Tool Box Lid (Lockable) Optional: Expanded Metal Tray Plate
- Spare Tire & Rim 215/75R17.5 (H) Optional: Spare Tire Carrier
- Traction 2" x 2" Angle 6" C/C Wheel Paths Optional: Traction Center Section, Bucket Pocket or Plate
- Ramps Wood (standard) Ladder (Optional N/C)
- Extension Ramps T-6 Alum. 22" x 75" 8-degree angle (SET)
- Apitong Decking in lieu of Oak
- Paint (other than standard Yellow) Price on Request