


# 35 GSL-S4S 35 Ton Self-Lifting Detachable Lowboy - ABS Air Brake Axles



**Capacity: 70,000 lbs. Trailer Weight: 15,500 lbs.**  
**Deck Width: 8 ft. 6 in. Length: 22 ft. Height: 24 in. (Loaded)**  
**80,000 lb. Minimum Yield Steel Mainframe**  
**Pierced Crossmembers**  
**Suspension: Hutch H-9700, 3 Leaf, Capacity 50,000**

**Front Flip Ramps**  
**Cast Steel Outriggers**  
**Patented "ROTO RINGS"® Swivel 360°**  
**100% Sealed Modular Wiring Harness**  
**Gooseneck 82" Std. (Add'l lengths available)**

## SPECIFICATIONS

Frame	Mainrails: Four fabricated 16" Deep cambered I-Beam, 80,000 P.S.I. steel
Crossmembers	10" x 9 lbs. per ft. I-Beam, pierced through mainbeam (24" spacing Std.)
Gooseneck Length	82", 86", 90", 94", 98" and 102" available (For special lengths contact sales)
Decking	Nominal 2" Hardwood
Wiring Harness	Sealed L.E.D. Lights & USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug
Front Ramps	Front Flip Steel w/ Grousers (Wood filled is available)
Hydraulics	Wetline hook-up for tractor PTO operation •REQUIREMENT: Low Flow/High Pressure System
Hydraulic Cylinders	Two Main 6", One 3" Locking, One 4" Gooseneck Support
Controls	Control Valve eye level
Tie Down	6 per side - Patented "ROTO RINGS"® Swivel 360°
Outriggers	Cast Steel (Locks both in and out position)
Colors	Yellow (Standard), Red, Black w/ matching RPC Undercoating

## RUNNING GEAR

Tires	Eight 255/70R22.5 (H) Michelin Steel Belted Radial
Hubs/Wheels	Four Disc Type Hubs, Eight 8.25 x 22.5 Disc Type Wheels, Stemco Oil Seals, Hub Piloted
Suspension	Hutch H-9700, three leaf, capacity 50,000 lbs. tandem (Adjustable Alignment)
Axles	Two 5" diameter 25,000 lbs. each, H.M. series bearings
Brakes	16 1/2" x 7" Air, "S" Cam., Auto Slack Adjusters
ALL WHEEL ABS	Anti-lock brake system 4S2M, Sensors on All Wheels, Two modulator valves
Parking Brake	Spring Brakes on All Wheels

## OPTIONS

Additional Deck Length or Width: (N/A for S4S model)  
 Wheel Covers (N/A for S4S model)  
 Power Pack: 11hp, 12hp Kohler, 13hp Honda, or 16hp Kohler (Combination Power Pack/Wet Kit Available)  
 Lockable Tool & Chain Storage: Forward center deck area (1 or 2 compartments)  
 Additional "ROTO-RINGS"®  
 Spare Tire & Disc Wheel 255/70R22.5 (H) Optional: Spare Tire Carrier  
 Tire & Disc Wheel 275/70R22.5 (H) Upgrade  
 Apitong Decking in lieu of Oak  
 Paint (other than standard Yellow) Price on Request